

Frame

Legs 1.25" square, 14-gauge steel adjustable legs with 1" square, 14-gauge inner tube on adjustable height stools; legs adjust using an Allen set screw. 1" square, 14-gauge steel legs on fixed height stools. Non-marring glides, 0.375" solid steel ring foot rest MIG welded. Weight load capacity is 750 lbs.

Backrest Optional 16-gauge steel bolt-on backrest.

Finish Black powder coated texture

Seats

Urethane Seat 14" round 1.93" urethane seat. Attaches with four 1/4"-20 x 1 3/8" joint connector bolts w/Loctite.

Hardwood Seat 14" round 1.25" face-glued hardwood strips, radius edge, two coats catalyzed lacquer finish. Attaches with (4) 1" Phillips head screws.

Lotz Armor Edge™ Seat 14" round 1.25" MDF top with high pressure laminate and phenolic backer sheet. Lotz Armor Edge™ is a polyurea, that is extremely strong and will not separate from the core. Attaches with (4) 1" Allen head machine screws.

Options

Steel Glides Optional steel glides available



STL7186-AQ4



STL9186-AF4



STLUR186-AF4

4-Legged Stools, No Backrest

Lotz AE™ Seat	AE™ Wgt	Hardwood Seat	Hardwood Wgt	Urethane Seat	Urethane Wgt	Description	Height" w/ Seat*
STL7186-AF4	13	STL9186-AF4	12	STLUR186-AF4	11	Desk Height Fx Stool	18
STL7186-AJ4	15	STL9186-AJ4	14	STLUR186-AJ4	13	Counter Height Fx Stool	24
STL7186-AQ4	20	STL9186-AQ4	19	STLUR186-AQ4	18	Table Height Adj Stool	18-28
STL7186-AM4	21	STL9186-AM4	20	STLUR186-AM4	19	Counter Height Adj Stool	22-32

*Seat height increases .5" with an urethane seat.



STL7186-AQ4-BZ



STL9186-AF4-BZ



STLUR186-AQ4-BZ

4-Legged Stools, Bolt-On Backrest

Lotz AE™ Seat	AE™ Wgt	Hardwood Seat	Hardwood Wgt	Urethane Seat	Urethane Wgt	Description	Height" w/ Seat*
STL7186-AF4-BZ	20	STL9186-AF4-BZ	19	STLUR186-AF4-BZ	18	Desk Height Fx Stool	18
STL7186-AJ4-BZ	22	STL9186-AJ4-BZ	21	STLUR186-AJ4-BZ	20	Counter Height Fx Stool	24
STL7186-AQ4-BZ	27	STL9186-AQ4-BZ	26	STLUR186-AQ4-BZ	25	Table Height Adj Stool	18-28
STL7186-AM4-BZ	28	STL9186-AM4-BZ	27	STLUR186-AM4-BZ	26	Counter Height Adj Stool	22-32

*Seat height increases .5" with an urethane seat.

Shipping Class: Frame: Density Based Class, Seat: 70

NMFC: Frame: 80580, Seat: 83620

Assembly: Some assembly required

Ground: Yes, with limitations, call Estimating