

Quad XL Workstation specifications

Lotz Armor Edge™ Tops:

Lotz Armor Edge™ top is constructed of 1.125" thick MDF (medium density fiberboard) core. MDF is a superior material for screw holding abilities exceeding 250 lbs., breaking strength and load tests. The back material is phenolic which **prevents moisture penetration** to core material and provides an anti gum surface. The top material is high pressure laminate that is bonded to the **MDF core** making the total thickness of the top at 1.25". The 0.25" beveled radius edge is finished using our exclusive Lotz Armor Edge™, a polyurea, which is extremely strong and durable. **This edge will not separate from the MDF core material and makes the edge water tight.** Lotz Armor Edge™ default is black. Premium colors available.



Standard Colors




Premium Colors



3mm Tops:

The core material is 1.125" thick particle board with a phenolic backer sheet and high pressure laminate on top making the total thickness of the top at 1.25". 3mm PVC edge banding* is applied to all sides, radius corners.



Optional top surface choices include **writable surface laminate** and most Wilsonart matte (60) finish laminates with possible up charges. Other vendors available upon request.

Shipping Class: Base: Density Based Class, Tops: 70
NMFC#: Base: 80440, Tops: 83620-2

Classic Construction:

Classic cabinets (sides, back, bottom and sub-top/sub-bottom) are constructed using fully doweled 0.75" particle board with double sided thermal fused laminate (TFL) with matching 3mm PVC edge banding. Unit consist of three cabinets that are attached together using joint connector bolts.

Doors are 0.75" double sided TFL, matching 3mm PVC edge banding, 4" satin nickel pulls and 6-point adjustable concealed hinges (European hinge).

Adjustable shelves are double sided TFL, matching 3mm PVC edge banding on front edge. Shelves have four double-pin shelf clips per shelf to prevent the shelves from sliding out or tipping.

Integrated, 1" caster base, matching 3mm PVC edge banding, 3" heavy-duty casters (six locking and six non-locking, casters are installed on site by others)

Dead bolt locks and connecting magnets for HangOut Stools are optional.

Assembly:

Each cabinet is factory assembled using glue and dowel construction, tops and casters need to be installed on site by others.

*3mm PVC edge banding is matching, unless otherwise specified. Complementary color available upon request.

Premium REplay® cabinets are constructed the same as the Classic **EXCEPT** the Premium cabinet components are double sided **high pressure laminate (HPL)** in place of the double sided TFL.


Example of Classic and Premium Model #'s:

Classic: CLQ7253-123230-AC/C
Premium: CLQ7253-123230-AC/P


Standard Features:



0.75" fully doweled casebody construction



4 double-pin clips with adjustable shelves



4" satin nickel pulls



3" heavy-duty locking & non-locking plate caster




6-point adjustable hinge


Optional Features:



Markerboard Top (-_MB)
Chemical resistant top (-09C)



Deadbolt locks



Connecting magnets for HangOut Stools, 4 locations (-4MA)

Quad XL Workstation



CLQ7253-123230-AC
Unit shown with a Premium finish.
Shown with optional Lotz Armor Edge™
and different colored edge banding.

Quad XL Workstation

2 cabinets w/ single door (each have 2 adj. shelves)
2 open cabinets (each have 2 adj. shelves)

Lotz AE™ Top	AE™ Wgt	3mm Top	3mm Wgt	Overall Hgt."	Top Dia"	Casebody W" x D"
CLQ7253-123230-AC	387	CLQ6253-123230-AC	381	30	60	45 x 45
CLQ7253-123236-AC	411	CLQ6253-123236-AC	405	36	60	45 x 45
CLQ7253-123240-AC	427	CLQ6253-123240-AC	421	40	60	45 x 45

of **OPTIONAL** locks required: 2

